

Secure View™ Smart Garage Opener with Built-in Camera

See clearly. Close securely.

84504R



PRODUCT GUIDE

LiftMaster
POWERED BY myQ.

Secure View™ Smart Garage Opener with Built-in Camera, Integrated Dual LED Lighting System, Battery Backup, Ultra-Quiet Belt Drive®

84504R



Popular features

Built-in Camera

- 130° wide angle camera that lets you monitor the garage through a live feed recorded event through the myQ® app
- Receive alerts and recordings in 1080p full HD video when motion is detected
- High Dynamic Range and Night Vision for greater image quality in high/low light environments
- Garage Climate Performance includes extreme climate operating range of -13 to 131°F

Smartphone Control

Control, secure and monitor the garage with the myQ app-anytime, from anywhere

Battery Backup

Lets you get in and out when the power is down

2-way communication

Hear what's happening in the garage. Includes adjustable volume and ability to enable or disable the mic through the myQ app

Quiet operation

An ultra-quiet DC motor and strong belt drive system ensures for comfortable living spaces near the garage


myQ Diagnostics Compatible

myQ Diagnostics in the myQ app provides real-time insights for your garage door via the Health Report. You will be sent alerts if an issue arises and you will be quickly connected to professional services if needed

Works with Amazon Key and Walmart+InHome

For convenient and secure In-Garage Delivery of Amazon and Walmart packages and groceries – watch deliveries happen in real-time





Do more with myQ

Use the myQ app to control, secure and monitor your garage and conveniently share and manage access to your home without sharing passcodes or keys. Also, take the hassle out of service repair and easily connect to a trusted Dealer through the myQ app.



Integrated dual LED lighting system

Increase the functionality of the garage and never change a garage light bulb again. Dual lighting system provides 1,500 lumens of long-lasting LED light that brightens high traffic areas of the garage.

In the box

893LM



3-Button Remote Control

Operates up to 3 openers or myQ light accessories. Safeguards your home with Security+ 2.0.

882LMW



Multi-Function Control Panel®

Operates the garage door opener and lights from inside the garage.

485LM



Garage Door Opener Battery

Integrated battery backup allows you to open and close your door even when the owner is out.

Specifications

Motor

12V DC, 53 RPM, automatic thermal protection

Mechanics

- Steel chassis, T-rail and trolley, full reinforced belt drive mechanism (63:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- Electronic limits for easy setup
- DC Wi-Fi logic board with built-in surge suppressor (for replacement logic boards, order part 050DCTBFMC)

Power

120V AC, 60 Hz voltage, 6A current rating, UL Listed, 4' power cord (3-prong)

Speed

7.2" per second upward, 7.2" per second downward

Lighting

Dual light lens LED - 1,500 lumens

Dimensions

Opener head: 10.5" L x 12.72" W x 8.185" H

Note: when both decorative doors are open, the width of the opener is 30".

Rail Options:	7' (2777BD)	8' (2778BD)	10' (2770BD)
Installed Length:	127"	139"	163"
Max Opening:	7' 6"	8' 6"	10' 6"

Headroom clearance required: 2"

Mounting

Side-to-Side

Warranties

Lifetime: Motor and Belt

1 Year: Parts, Camera, Accessories and LED

Security+ 2.0

Radio controls:

Operating range ~200'; Operating temperature: -40F to 150F; 3-Button Remote Control (893LM), Remote Control Code Format: Security+2.0, premium remote control; Garage Door Opener Code Format: Security+2.0; Anti-burglary coding.

Encrypted controls:

Multi-Function Control Panel (882LMW);

Program remote controls, maintenance alert system, easy Wi-Fi set up.

myQ Radio

902-928 MHz 50-Channel FHSS (frequently hopping spread spectrum); Provides 2-way communication from garage door opener and myQ accessories; Enables monitoring and control of garage door openers via smartphone or tablet.

HomeLink® compatible (version 4.0 or higher)

May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information.

Carton 1 shipping details

Dimensions: 14" x 12" x 11"

Contents: Garage Door Opener Head (84505R), Multi-Function Control Panel (882LMW), Battery Backup (485LM), 3-Button Remote Control (893LM), The Protector System® Safety Reversing Sensors
Weight: 22.8 lbs.

Carton 2 shipping details

Dimensions: 10'4" x 5" x 5" (for 7' rail)

Contents: Assembled Solid-Steel Belt T-Rail
Weight: 17 lbs.

For purchase and professional install

Visit LiftMaster.com

For partners

Orders: 800.282.6225 | Support: 800.528.2806 | Self service: LiftMasterTraining.com

© 2023 The Chamberlain Group, LLC. All Rights Reserved.

LiftMaster, the Liftmaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, LLC. UL® and the UL logo are trademarks of UL LLC. Wi-Fi® is a registered trademark of Wi-Fi Alliance. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.
LMGDENPG84504R 04/23